

17 Harrison Street  
Marshalltown

P O Box 61542  
Marshalltown 2107  
Tel : (011) 688-1400 Fax : (011) 688-1556



**REQUEST FOR QUOTATION**

INITIATING DEPARTMENT	INITIATOR
METERING - FFENNEL ROAD	V. MOODLEY
QUOTATION REFERENCE	COLLECTIVE NO.
<b>JW0081 MC 2020 OF STAINLESS STEEL ENCLOSURES</b>	
QUOTATION REQUESTED FROM	

JW CONTACT PERSON:.....Maria Chirindze.....

TELEPHONE NUMBER:.....688 6610.....

QUOTATION VALIDITY
2020-10-08

PAGE NO.	1
CLOSING DATE AND TIME	26-Aug-20 16:00:00 PM
Date of Issue	19 August 2020
VALIDITY	7: DAYS

ITEM NO.	DESCRIPTION	BRAND NAME OFFERED	UOM	QTY REQUIRED	PRICE QUOTED EXCL. OF V.A.T.	DIS
1	MANUFACTURE, SUPPLY AND DELIVERY OF STAINLESS STEEL ENCLOSURES WITH A 3-WAY SMART LOCKING SYSTEM TO HOUSE VARIOUS INSTRUMENT AND ELECTRICAL COMPONENTS			16		
	<b>STEEL ENCLOSURE SPECIFICATION</b>					
	THE DIMENSIONS OF THE STEEL ENCLOSURE MUST BE OF LENGTH 1350 x DEPTH 450 X WIDTH 500					
	THE DESIGN IS SPECIFIC IN THAT IT SHOULD BE TAMPERPROOF WITH NO VISIBLE DOOR					
	THE LOCK SHOULD ALSO BE CONCEALED					
	THE LOCKING MECHANISM SHOULD BE UNIQUE IN THAT IT MUST HAVE A SPRING LOADED MECHANISM WHICH SHOULD BE MOUNTED INTERNALLY AND MUST OPEN WITH A UNIQUE KEY FOR ALL CUBICLES					
	THE STAINLESS STEEL MUST BE 2.5MM THICK AND LIGHT GREY POWDER COATED					
	THE ENCLOSURE MUST BE FITTED WITH A BACKPLATE FOR THE MOUNTING OF ENCLOSURES					
	THE ENCLOSURE SHOULD ALSO HAVE SPECIAL AIR VENTS AND INSULATED MATERIAL TO KEEP THE ELECTRICAL AND INSTRUMENTATION COOL					
	THE BASE OF THE ENCLOSURE SHOULD HAVE A HOLE AT EACH CORNER TO ENSURE THAT IT CAN BE MOUNTED ONTO A PRECAST CONCRETE BASE					
	ATTACHED, PLEASE FIND A DRAWING OF THE ENCLOSURE					
	<b>NB:All suppliers responding to Rfq's should use their own company letter head not Jw Rfq Template AND MAKE SURE THEIR EMAIL ADDRESS IS VISIBLE ON THEIR QUOTATION.send Quate to maria.chirindze@jwater.co.za</b>					

OFFICIAL STAMP	SUPPLIER DETAILS
	AUTHORISED BY: .....
	SIGNATURE:.....
	DATE:.....

<b>CONDITIONS</b>
1. QUOTATIONS RECEIVED AFTER CLOSE OF BUSINESS ON THE CLOSING DATE WILL NOT BE ACCEPTED.
2. QUOTATIONS WITHOUT BRAND NAMES WHERE REQUIRED WILL NOT BE ACCEPTED
3. PRICES QUOTED MUST BE AS PER THE UNIT INDICATED AND BE EXCLUDED OF VAT
4 QUOTATIONS WITHOUT THE SUPPLIER'S AUTHORISED SIGNATURE WILL NOT BE ACCEPTED.
5 ACCEPTANCE OF A QUOTATION WILL BE SUBJECT TO JOHANNESBURG WATER'S SUPPLY CHAIN POLICY

## Re: Steel Enclosure with 3 Way Smart locking

### Smart lock loaded mechanism:

The loaded mechanism is attached to the Smartlock and is designed to automatically clip into the roof mountings. The spring loaded system on the mechanism is used in case the lock is damaged and will instantaneously lock the unit under protection. The lock is further protected by a cast cover. The curved outer shell of the cover makes it impossible to be cut through ensuring that the only thing getting close to the inner lock is the key.

### Cubicle:

The cubicle is specially designed with hidden doors and sliding panels to prevent any tampering from the outside. There are no visible doors or locks that can be damaged.

The cubicle is insulated with polystyrene and special air vents are included to reduce the buildup of heat to keep the instruments cool.

The cubicle is fitted with a back plate, gear tray.

